

View Online at <https://aerobasegroup.com/nsn/5915-00-322-9192>

Overall Height:

0.900 inches

Body Length:

2.750 inches

Body Width:

0.850 inches

Body Height:

0.550 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.800 inches

Vibration Resistance Range In Hertz:

+20.0 to 2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.200 inches

Operating Temperature Range:

-40.0 to 131.0 degrees fahrenheit

Reference Frequency Per Function:

455.0 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud 1st function

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

454.60 kilohertz blank and 454.90 kilohertz blank and 455.10 kilohertz blank and 455.40 kilohertz blank

Frequency Band Width Per Function:

454.90 kilohertz blank and 455.10 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 3.0 blank and 3.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0