

View Online at <https://aerobasegroup.com/nsn/5915-00-348-6856>

Overall Length:

2.094 inches

Overall Height:

0.844 inches

Body Length:

1.875 inches

Body Width:

0.875 inches

Body Height:

0.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Average Life Rating In Hours:

1000.0

Reference Frequency Per Function:

500.0 kilohertz blank

Input Impedance Per Function W/load:

1.5 kilohms blank

Output Impedance Per Function W/source Across Input:

1.5 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

365.00 kilohertz blank and 457.00 kilohertz blank and 543.00 kilohertz blank and 635.00 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

457.00 kilohertz blank and 543.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 3.0 blank and 3.0 blank and 30.0 blank

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0