

View Online at https://aerobasegroup.com/nsn/5915-00-350-8195

| Overall Length: |
|--|
| 2.500 inches |
| Body Length: |
| 2.000 inches |
| Body Width: |
| 2.500 inches |
| |
| Body Height: 2.000 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.500 inches |
| |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Source Impedance Rating Per Function: |
| |
| Load Impedance Per Function: 50.0 ohms 2nd radio interference |
| |
| Power Line Frequency Rating Per Function In Hertz: 400.0 3rd radio interference |
| Operating Current Rating Per Function In Amps: |
| 1.0 2nd radio interference |
| |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance 3rd radio interference |
| Input Terminal Manufacturer Code: 96906 |
| |
| Input Terminal Identification: |
| Ms3112e-8-4s |
| Mounting Facility Screw Thread Series Designator: |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 threaded hole |
| Functional Terminal Type And Quantity: |
| 2 tab, solder lug output 2nd function |
| Operating Voltage Rating And Type Per Function: |
| 115.0 volts ac 3rd radio interference 3rd function |
| Thread Size: |
| 0.138 inches |
| |
| Body Material: Metal |
| |
| Style Designator: |
| Rectangular terminal/terminals on opposite surfaces |

Radio Frequency Interference Filter - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0