NSN 5915-00-351-0013

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-351-0013

Overall Height:
2.062 inches
Body Length:
Between 1.625 inches and 1.687 inches
Body Width:
Between 1.125 inches and 1.187 inches
Body Height:
Between 1.500 inches and 1.625 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
-40.0/+65.0 degrees celsius
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
2.0725 kilohertz blank
Source Impedance Rating Per Function:
600.0 ohms blank
Load Impedance Per Function:
600.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
1 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 blank
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Specified Frequencies Of Discrimination Per Function:
1.995 kilohertz blank and 2.150 kilohertz blank and 2.50 kilohertz blank and 2.975 kilohertz blank
Thread Size:
0.138 inches
Frequency Band Width Per Function:

1.995 kilohertz blank and 2.150 kilohertz blank

NSN 5915-00-351-0013

Low Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 18.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0