

View Online at <https://aerobasegroup.com/nsn/5915-00-356-2160>

Overall Height:

Between 3.088 inches and 3.110 inches

Body Length:

Between 2.500 inches and 2.562 inches

Body Width:

Between 1.407 inches and 1.469 inches

Body Height:

Between 2.532 inches and 2.656 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.296 inches and 1.328 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.938 inches

Operating Temperature Range:

-65.0/+185.0 degrees celsius

Reference Frequency Per Function:

20.0 kilohertz blank

Input Impedance Per Function W/load:

135.0 ohms blank

Output Impedance Per Function W/source Across Input:

135.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

5.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Specified Frequencies Of Discrimination Per Function:

16.00 kilohertz blank and 19.00 kilohertz blank and 21.00 kilohertz blank and 24.00 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

19.00 kilohertz blank and 21.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 20.0 blank and 20.0 blank and 55.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0