

View Online at <https://aerobasegroup.com/nsn/5915-00-356-2160>

**Overall Height:**

Between 3.088 inches and 3.110 inches

**Body Length:**

Between 2.500 inches and 2.562 inches

**Body Width:**

Between 1.407 inches and 1.469 inches

**Body Height:**

Between 2.532 inches and 2.656 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.296 inches and 1.328 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.938 inches

**Operating Temperature Range:**

-65.0/+185.0 degrees celsius

**Reference Frequency Per Function:**

20.0 kilohertz blank

**Input Impedance Per Function W/load:**

135.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

135.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

5.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

16.00 kilohertz blank and 19.00 kilohertz blank and 21.00 kilohertz blank and 24.00 kilohertz blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

19.00 kilohertz blank and 21.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

60.0 blank and 20.0 blank and 20.0 blank and 55.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0