

View Online at <https://aerobasegroup.com/nsn/5915-00-361-9148>

Overall Height:

0.750 inches

Body Length:

1.953 inches

Body Width:

0.594 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.600 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.250 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

75.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 pin output 2nd function

Specified Frequencies Of Discrimination Per Function:

74.88 megahertz blank and 74.9775 megahertz blank and 75.0225 megahertz blank and 75.12 megahertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

74.9775 megahertz blank and 75.0225 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0