

View Online at https://aerobasegroup.com/nsn/5915-00-369-7667

Overall Length:
1.192 inches
Body Length:
0.540 inches
Body Outside Diameter:
0.375 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Rating In Hours:
250.0
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
10.0 blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Manualian Facility Consul Thread Conice Decimation
Mounting Facility Screw Thread Series Designator:
Unf
Unf
Unf Inclosure Type:
Unf Inclosure Type: Hermetically sealed
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Inductor at mounting end
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 0 perating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Inductor at mounting end Style Designator:
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 50.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 100.0 volts at sea level Special Features: Inductor at mounting end Style Designator: Round terminal/terminals on opposite surfaces

---



Demilitarization:

No

Fiig:

A047b0