## NSN 5915-00-375-2328

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-375-2328

| Overall Height:                                                                                     |
|-----------------------------------------------------------------------------------------------------|
| 2.750 inches                                                                                        |
| Body Length:                                                                                        |
| 1.375 inches                                                                                        |
| Body Width:                                                                                         |
| 0.969 inches                                                                                        |
| Body Height:                                                                                        |
| 2.188 inches                                                                                        |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:                        |
| 3.500 inches                                                                                        |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                         |
| 0.375 inches                                                                                        |
| Reference Frequency Per Function:                                                                   |
| 34.0 kilohertz blank                                                                                |
| Source Impedance Rating Per Function:                                                               |
| 50.0 kilohms blank                                                                                  |
| Input Impedance Per Function W/load:                                                                |
| 50.0 kilohms blank                                                                                  |
| Output Impedance Per Function W/source Across Input:                                                |
| 100.0 kilohms blank                                                                                 |
| Principal Circuitry Type Per Function:                                                              |
| Inductance-capacitance blank                                                                        |
| Mounting Facility Screw Thread Series Designator:                                                   |
| Unc                                                                                                 |
| Inclosure Type:                                                                                     |
| Encased                                                                                             |
| Mounting Facility Type And Quantity:                                                                |
| 1 threaded stud                                                                                     |
| Insertion Loss At Reference Frequency Per Function In Decibels:                                     |
| 3.0 blank                                                                                           |
| Functional Terminal Type And Quantity:                                                              |
| 2 tab, solder lug output 2nd function                                                               |
| Specified Frequencies Of Discrimination Per Function:                                               |
| 28.50 kilohertz blank and 30.25 kilohertz blank and 37.75 kilohertz blank and 39.50 kilohertz blank |
| Thread Size:                                                                                        |
| 0.138 inches                                                                                        |
| Frequency Band Width Per Function:                                                                  |
| 30.25 kilohertz blank and 37.75 kilohertz blank                                                     |
| Discrimination At Specificationified Frequencies Per Function In Decibels:                          |
| 30.0 blank and 3.0 blank and 30.0 blank                                                             |
|                                                                                                     |

Style Designator:

Rectangular terminal/terminals on one surface

## NSN 5915-00-375-2328

Band Pass Filter - Page 2 of 2



| _ |     |      |   |      |
|---|-----|------|---|------|
| c | hο  | JIF. |   | ife: |
| J | 116 |      | _ | HG.  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0