

View Online at https://aerobasegroup.com/nsn/5915-00-400-1816

Overall Length:
4.000 inches
Body Length:
Between 3.500 inches and 3.620 inches
Body Outside Diameter:
Between 1.115 inches and 1.145 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
0.5 blank
Maximum Voltage Drop Per Function:
2.5 volts ac blank and 6.0 volts dc blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 1 threaded bushing
1 threaded bushing
1 threaded bushing Functional Terminal Type And Quantity:
 threaded bushing Functional Terminal Type And Quantity: tab, solder lug output 2nd function
 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage:
 threaded bushing Functional Terminal Type And Quantity: tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level
 threaded bushing Functional Terminal Type And Quantity: tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function:
 threaded bushing Functional Terminal Type And Quantity: tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank
 threaded bushing Functional Terminal Type And Quantity: tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank Thread Size:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank Thread Size: 0.437 inches
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank Thread Size: 0.437 inches Maximum Dielectric Withstanding Dc Voltage:
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank Thread Size: 0.437 inches Maximum Dielectric Withstanding Dc Voltage: 1.2 kilovolts at sea level Style Designator: Round terminal/terminals on opposite surfaces
 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank Thread Size: 0.437 inches Maximum Dielectric Withstanding Dc Voltage: 1.2 kilovolts at sea level
1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Maximum Dielectric Withstanding Ac Rms Voltage: 500.0 volts at sea level Operating Voltage Rating And Type Per Function: 600.0 volts ac blank and 250.0 volts dc blank Thread Size: 0.437 inches Maximum Dielectric Withstanding Dc Voltage: 1.2 kilovolts at sea level Style Designator: Round terminal/terminals on opposite surfaces



Demilitarization:

Yes - demil/mli

Fiig:

A047b0