NSN 5915-00-403-1417

Band Pass Filter - Page 1 of 2

Overall Height: 0.760 inches Body Length: 2.500 inches Body Width: 2.500 inches Body Height:

N/a



View Online at https://aerobasegroup.com/nsn/5915-00-403-1417

0.625 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:					
1.400 inches					
Vibration Resistance Range In Hertz:					
+10.0/+55.0					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:					
1.400 inches					
Operating Tempurature Range:					
+0.0/+65.0 degrees celsius					
Reference Frequency Per Function:					
13.0 kilohertz blank					
Source Impedance Rating Per Function:					
50.0 ohms blank					
Load Impedance Per Function:					
50.0 ohms blank					
Inclosure Type:					
Encapsulated					
Mounting Facility Type And Quantity:					
4 terminal					
4 terminal Insertion Loss At Reference Frequency Per Function In Decibels:					
Insertion Loss At Reference Frequency Per Function In Decibels:					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity:					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function:					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank Body Material:					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank Body Material: Metal					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank Body Material: Metal Frequency Band Width Per Function:					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank Body Material: Metal Frequency Band Width Per Function: 10.20 kilohertz blank and 15.50 kilohertz blank					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank Body Material: Metal Frequency Band Width Per Function: 10.20 kilohertz blank and 15.50 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:					
Insertion Loss At Reference Frequency Per Function In Decibels: 9.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 5.70 kilohertz blank and 10.20 kilohertz blank and 15.50 kilohertz blank and 16.90 kilohertz blank Body Material: Metal Frequency Band Width Per Function: 10.20 kilohertz blank and 15.50 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank					

NSN 5915-00-403-1417

Band Pass Filter - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A047b0