# NSN 5915-00-406-3959

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-406-3959

Overall Length:
5.750 inches
Body Length:
4.250 inches
Body Width:
1.620 inches
Body Height:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
3.750 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.620 inches
Operating Tempurature Range:
-54.0/+70.0 degrees celsius
Reference Frequency Per Function:
135.0 megahertz blank
Input Impedance Per Function W/load:
50.0 ohms blank
Output Impedance Per Function W/source Across Input:
50.0 ohms blank
Input Terminal Manufacturer Code:
27834
Input Terminal Identification:
N
Output Terminal Manufacturer Code:
27834
Output Terminal Identification:
N
Voltage Standing Wave Ratio Per Function:
1.30 blank
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 unthreaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
0.5 blank
Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

## NSN 5915-00-406-3959

Low Pass Filter - Page 2 of 2



### **Specified Frequencies Of Discrimination Per Function:**

116.00 megahertz blank and 150.00 megahertz blank and 232.00 megahertz blank and 1.00 gigahertz blank

### **Frequency Band Width Per Function:**

116.00 megahertz blank and 150.00 megahertz blank

### Discrimination At Specificationified Frequencies Per Function In Decibels:

0.5 blank and 0.5 blank and 50.0 blank and 50.0 blank

**Style Designator:** 

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A047b0