NSN 5915-00-411-6174

Low Pass Filter - Page 1 of 2

0.00 hertz blank and 70.00 kilohertz blank



View Online at https://aerobasegroup.com/nsn/5915-00-411-6174

Overall Height:
2.130 inches
Body Length:
1.310 inches
Body Width:
1.310 inches
Body Height:
1.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Operating Tempurature Range:
-28.0/+65.0 degrees celsius
Reference Frequency Per Function:
35.0 kilohertz blank
Source Impedance Rating Per Function:
10.0 kilohms blank
Load Impedance Per Function:
10.0 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
2 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 wire hook output 2nd function
Maximum Dielectric Withstanding Ac Rms Voltage:
500.0 volts at sea level
Specified Frequencies Of Discrimination Per Function:
0.00 hertz blank and 70.00 kilohertz blank and 119.00 kilohertz blank and 238.00 kilohertz blank
Thread Size:
0.138 inches
Body Material:
Metal
Frequency Band Width Per Function:

NSN 5915-00-411-6174

Low Pass Filter - Page 2 of 2



Discrimination At Speci	ficationified Frequ	ıencies Per Fu	ınction In Decibels:
--------------------------------	---------------------	----------------	----------------------

3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0