# NSN 5915-00-411-6174

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-411-6174

## **Overall Height:**

2.130 inches

#### Body Length:

1.310 inches

#### Body Width:

1.310 inches

#### **Body Height:**

#### 1.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 1.250 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

## 1.250 inches

## **Operating Tempurature Range:**

## -28.0/+65.0 degrees celsius

## **Reference Frequency Per Function:**

## 35.0 kilohertz blank

## Source Impedance Rating Per Function:

## 10.0 kilohms blank

## Load Impedance Per Function:

10.0 kilohms blank

## Principal Circuitry Type Per Function:

Inductance-capacitance blank

## Mounting Facility Screw Thread Series Designator:

Unc

## Inclosure Type:

Hermetically sealed

## Mounting Facility Type And Quantity:

2 threaded stud

## Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

## Functional Terminal Type And Quantity:

1 wire hook output 2nd function

## Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

## Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 70.00 kilohertz blank and 119.00 kilohertz blank and 238.00 kilohertz blank

#### Thread Size:

0.138 inches

## **Body Material:**

Metal

## Frequency Band Width Per Function:

0.00 hertz blank and 70.00 kilohertz blank

## NSN 5915-00-411-6174

Low Pass Filter - Page 2 of 2



#### Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 3.0 blank and 60.0 blank and 60.0 blank

#### Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A047b0