

View Online at <https://aerobasegroup.com/nsn/5915-00-414-1654>

Overall Height:

6.440 inches

Body Length:

2.220 inches

Body Width:

1.350 inches

Body Height:

5.970 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.750 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.880 inches

Operating Tempurature Range:

+0.0/+65.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

74.0 kilohertz blank

Source Impedance Rating Per Function:

600.0 ohms blank

Load Impedance Per Function:

600.0 ohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

4.5 blank

Functional Terminal Type And Quantity:

2 turret input 1st function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

63.00 kilohertz blank and 69.875 kilohertz blank and 78.125 kilohertz blank and 85.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

69.875 kilohertz blank and 78.125 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

80.0 blank and 3.0 blank and 3.0 blank and 80.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0