

View Online at <https://aerobasegroup.com/nsn/5915-00-418-3573>

Overall Height:

3.441 inches

Body Length:

2.250 inches

Body Width:

2.000 inches

Body Height:

3.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.688 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.438 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

3.5 kilohertz blank

Source Impedance Rating Per Function:

1.0 kilohms blank

Load Impedance Per Function:

1.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

12.0 blank

Functional Terminal Type And Quantity:

1 turret output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

100.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

3.14 kilohertz blank and 3.36 kilohertz blank and 3.70 kilohertz blank and 3.86 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

3.36 kilohertz blank and 3.70 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

55.0 blank and 1.0 blank and 1.0 blank and 55.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0