

View Online at <https://aerobasegroup.com/nsn/5915-00-419-7209>

Overall Height:

1.500 inches

Body Length:

0.719 inches

Body Width:

0.719 inches

Body Height:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.500 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

22.0 kilohertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encapsulated

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

2 pin output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

12.76 kilohertz blank and 20.35 kilohertz blank and 23.65 kilohertz blank and 38.50 kilohertz blank

Body Material:

Metal

Frequency Band Width Per Function:

20.35 kilohertz blank and 23.65 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0