

View Online at <https://aerobasegroup.com/nsn/5915-00-419-7209>

**Overall Height:**

1.500 inches

**Body Length:**

0.719 inches

**Body Width:**

0.719 inches

**Body Height:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.500 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

22.0 kilohertz blank

**Source Impedance Rating Per Function:**

10.0 kilohms blank

**Load Impedance Per Function:**

10.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Inclosure Type:**

Encapsulated

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

2 pin output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

12.76 kilohertz blank and 20.35 kilohertz blank and 23.65 kilohertz blank and 38.50 kilohertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

20.35 kilohertz blank and 23.65 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0