

View Online at <https://aerobasegroup.com/nsn/5915-00-430-5104>

**Overall Height:**

1.110 inches

**Body Length:**

3.375 inches

**Body Width:**

1.032 inches

**Body Height:**

0.800 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.936 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.562 inches

**Operating Temperature Range:**

-54.0/+70.0 degrees celsius

**Reference Frequency Per Function:**

20.6 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

31550

**Output Terminal Identification:**

Sma-receptacle

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Features Provided:**

Shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.5 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

20.30 megahertz blank and 20.567 megahertz blank and 20.633 megahertz blank and 20.90 megahertz blank

**Thread Size:**

0.112 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

20.567 megahertz blank and 20.633 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 100.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0