

View Online at <https://aerobasegroup.com/nsn/5915-00-448-9410>

Overall Height:

0.795 inches

Body Length:

2.750 inches

Body Width:

1.875 inches

Body Height:

0.690 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.350 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-54.0/+100.0 degrees celsius

Reference Frequency Per Function:

251.5 kilohertz blank

Input Impedance Per Function W/load:

500.0 ohms blank

Output Impedance Per Function W/source Across Input:

500.0 ohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

248.70 kilohertz blank and 249.00 kilohertz blank and 254.00 kilohertz blank and 259.00 kilohertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

249.00 kilohertz blank and 254.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 1.0 blank and 1.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

13499-293-1196-020 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0