NSN 5915-00-449-0732

High Pass-low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-449-0732 **Overall Length:** 16.000 inches **Overall Height:** 6.000 inches Overall Width: 2.500 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.250 inches **End Application:** Filter assembly f-1288/frc **Reference Frequency Per Function:** 12.3 7th radio interference any acceptable **Source Impedance Rating Per Function:** 75.0 ohms single low pass **Load Impedance Per Function:** 75.0 ohms single low pass **Principal Circuitry Type Per Function:** Inductance-capacitance single low pass **Inclosure Type:** Hermetically sealed **Mounting Facility Type And Quantity:** 4 unthreaded hole **Features Provided:** Magnetic case and moisture resistant Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 single low pass **Specified Frequencies Of Discrimination Per Function:** 1.00 hertz single low pass and 5.85 kilohertz single low pass and 11.70 kilohertz single low pass and 23.40 kilohertz single low pass **Body Material:** Metal **Frequency Band Width Per Function:** 1.00 hertz single low pass and 12.30 kilohertz single low pass Discrimination At Specificationified Frequencies Per Function In Decibels: 3.0 single low pass and 60.0 single low pass

N/a
Unit Of Measure:

Shelf Life:

NSN 5915-00-449-0732

High Pass-low Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0