

View Online at <https://aerobasegroup.com/nsn/5915-00-451-7318>

**Overall Length:**

17.020 inches

**Overall Height:**

3.500 inches

**Body Length:**

13.000 inches

**Body Width:**

12.000 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

11.000 inches

**Vibration Resistance Range In Hertz:**

+5.0/+33.0

**Operating Temperature Range:**

-55.0/+80.0 degrees celsius

**Source Impedance Rating Per Function:**

150.0 ohms 2nd radio interference

**Load Impedance Per Function:**

150.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

60.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

60.0 1st radio interference

**Maximum Voltage Drop Per Function:**

1.0 volts ac 1st radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance-resistance 1st radio interference

**Maximum Temperature Rise:**

28.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

0.015 and 0.15 and 0.5 and 1.0 and 10.0 and 100.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

48.0 and 100.0 and 100.0 and 100.0 and 100.0 and 80.0

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

10 unthreaded hole

**Functional Terminal Type And Quantity:**

2 threaded stud input 1st function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

800.0 volts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

2.875 in. Distance between mtg holes parallel to body h

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Test Data Document:**

03640-2989855 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0