

View Online at <https://aerobasegroup.com/nsn/5915-00-456-3435>

**Overall Length:**

3.374 inches

**Body Length:**

3.062 inches

**Body Width:**

2.875 inches

**Body Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.500 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 4th radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 4th radio interference

**Operating Current Rating Per Function In Amps:**

1.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.25 volts ac 4th radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference

**Full Load Insertion Loss Frequencies In Megahertz:**

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

7.0 and 7.0 and 7.0 and 7.0 and 60.0 and 60.0

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Moisture resistant and shock resistant

**Functional Terminal Type And Quantity:**

4 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

250.0 volts at sea level

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac 1st radio interference 1st function

**Thread Size:**

0.138 inches

**Body Material:**

Metal

**Body Surface Treatment:**

Tin

**Special Features:**

Four filtered functions

**Unpackaged Unit Weight:**

12.000 ounces

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0