

View Online at <https://aerobasegroup.com/nsn/5915-00-456-3435>

Overall Length:

3.374 inches

Body Length:

3.062 inches

Body Width:

2.875 inches

Body Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.500 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 4th radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 4th radio interference

Operating Current Rating Per Function In Amps:

1.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.25 volts ac 4th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 3rd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

7.0 and 7.0 and 7.0 and 7.0 and 60.0 and 60.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Moisture resistant and shock resistant

Functional Terminal Type And Quantity:

4 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

250.0 volts at sea level

Operating Voltage Rating And Type Per Function:

125.0 volts ac 1st radio interference 1st function

Thread Size:

0.138 inches

Body Material:

Metal

Body Surface Treatment:

Tin

Special Features:

Four filtered functions

Unpackaged Unit Weight:

12.000 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0