

View Online at https://aerobasegroup.com/nsn/5915-00-457-7960

Overall Length: 1.626 inches Body Length: 1.014 inches Body Outside Diameter: 0.406 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function:
Body Length: 1.014 inches Body Outside Diameter: 0.406 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
1.014 inches Body Outside Diameter: 0.406 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
Body Outside Diameter: 0.406 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
0.406 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
Vibration Resistance Range In Hertz: +10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
+10.0/+2000.0 Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
Operating Tempurature Range: -55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
-55.0/+85.0 degrees celsius Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
Average Life Rating In Hours: 250.0 Source Impedance Rating Per Function: 50.0 ohms blank
250.0 Source Impedance Rating Per Function: 50.0 ohms blank
Source Impedance Rating Per Function: 50.0 ohms blank
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
40.0 blank
Operating Current Rating Per Function In Amps:
1.0 blank and 1.0 blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
115.0 volts ac blank and 400.0 volts dc blank
Thread Size:
0.250 inches
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
600.0 volts at sea level
Precious Material And Location:
Finish case gold
Precious Material:
Gold



Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0