

View Online at <https://aerobasegroup.com/nsn/5915-00-460-4410>

Overall Height:

3.562 inches

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

3.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.704 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.454 inches

Operating Temperature Range:

+0.0/+105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

10.5 kilohertz blank

Input Impedance Per Function W/load:

600.0 ohms blank

Output Impedance Per Function W/source Across Input:

600.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

50.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

4.50 kilohertz blank and 9.70 kilohertz blank and 11.20 kilohertz blank and 20.00 kilohertz blank

Thread Size:

0.138 inches

Body Material:

Metal

Frequency Band Width Per Function:

9.70 kilohertz blank and 11.20 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 6.0 blank and 6.0 blank and 40.0 blank

Maximum Dielectric Withstanding Dc Voltage:

50.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0