## NSN 5915-00-470-8289

9.60 gigahertz blank and 13.70 gigahertz blank

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-470-8289

Overall Height:
0.650 inches
Body Length:
1.950 inches
Body Width:
0.500 inches
Body Height:
0.650 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.200 inches
Vibration Resistance Range In Hertz:
+30.0/+2000.0
Operating Tempurature Range:
-54.0/+125.0 degrees celsius
Average Life Rating In Hours:
2000.0
Reference Frequency Per Function:
11.65 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
1.7 blank
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
1 threaded hole
Screw Thready Qty Per Inch (tpi):
40
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 receptacle, coaxial input 1st function
Specified Frequencies Of Discrimination Per Function:
9.60 gigahertz blank and 13.70 gigahertz blank and 14.60 gigahertz blank and 18.00 gigahertz blank
Frequency Band Width Per Function:

## NSN 5915-00-470-8289

Low Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 1.0 blank and 40.0 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:** 

9.6 gigahertz blank and 13.7 gigahertz blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0