

View Online at https://aerobasegroup.com/nsn/5915-00-471-4000

Overall Length:
1.223 inches
Body Length:
0.571 inches
Body Outside Diameter:
0.375 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Rating In Hours:
250.0
Input Impedance Per Function W/load:
50.0 ohms blank
Output Impedance Per Function W/source Across Input:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
1.0 blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Mounting Facility Screw Thread Series Designator:
Unf
Unf Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 200.0 volts at sea level
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 200.0 volts at sea level Special Features:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 200.0 volts at sea level Special Features: Inductor at mounting end
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 200.0 volts at sea level Special Features: Inductor at mounting end Style Designator:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 100.0 volts dc blank Thread Size: 0.250 inches Maximum Dielectric Withstanding Dc Voltage: 200.0 volts at sea level Special Features: Inductor at mounting end Style Designator: Round terminal/terminals on opposite surfaces

Radio Frequency Interference Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0