## NSN 5915-00-471-5186

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-471-5186

Overall Height:
0.960 inches
Body Length:
2.300 inches
Body Width:
1.000 inches
Body Height:
0.740 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.950 inches
Vibration Resistance Range In Hertz:
+5.0/+50.0
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Reference Frequency Per Function:
24.371 kilohertz blank
Source Impedance Rating Per Function:
1.0 kilohms blank
Load Impedance Per Function:
1.0 kilohms blank
Mounting Facility Screw Thread Series Designator:
Unc
Offic
Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank Thread Size: 0.112 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function:
Inclosure Type: Hermetically sealed  Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 24.361 kilohertz blank and 24.381 kilohertz blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 24.361 kilohertz blank and 24.381 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 2 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 4.0 blank Functional Terminal Type And Quantity: 2 pin ground 3rd function Specified Frequencies Of Discrimination Per Function: 23.472 kilohertz blank and 24.361 kilohertz blank and 24.381 kilohertz blank and 25.00 kilohertz blank Thread Size: 0.112 inches Frequency Band Width Per Function: 24.361 kilohertz blank and 24.381 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 80.0 blank and 3.0 blank and 3.0 blank and 80.0 blank

N/a

## NSN 5915-00-471-5186

Band Pass Filter - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A047b0