

View Online at <https://aerobasegroup.com/nsn/5915-00-475-4888>

Overall Height:

Between 1.938 inches and 2.062 inches

Body Length:

Between 1.683 inches and 1.693 inches

Body Width:

Between 1.157 inches and 1.219 inches

Body Height:

Between 1.594 inches and 1.656 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.234 inches and 1.266 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.734 inches and 0.766 inches

Reference Frequency Per Function:

250.0 hertz blank

Source Impedance Rating Per Function:

10.0 kilohms blank

Load Impedance Per Function:

10.0 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

10.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-resistance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Specified Frequencies Of Discrimination Per Function:

125.00 hertz blank and 242.50 hertz blank and 257.50 hertz blank and 500.00 hertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

242.50 hertz blank and 257.50 hertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

35.0 blank and 2.0 blank and 2.0 blank and 35.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0