## NSN 5915-00-475-7276

Band Pass Filter - Page 1 of 2

6.20 gigahertz blank and 9.50 gigahertz blank



View Online at https://aerobasegroup.com/nsn/5915-00-475-7276

Overall Length:
3.080 inches
Overall Height:
1.280 inches
Body Length:
3.080 inches
Body Width:
0.450 inches
Body Height:
0.900 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.840 inches
Vibration Resistance Range In Hertz:
+30.0/+2000.0
Operating Tempurature Range:
-54.0/+125.0 degrees celsius
Average Life Rating In Hours:
2000.0
Reference Frequency Per Function:
7.85 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Voltage Standing Wave Ratio Per Function:
2.0 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
1 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
5.99 gigahertz blank and 6.20 gigahertz blank and 9.50 gigahertz blank and 9.70 gigahertz blank
Thread Size:
0.112 inches
Frequency Band Width Per Function:

## NSN 5915-00-475-7276

Band Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 1.5 blank and 1.5 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:** 

6.2 gigahertz blank and 9.5 gigahertz blank

**Style Designator:** 

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0