

View Online at https://aerobasegroup.com/nsn/5915-00-481-5081

Overall Length:1.073 inchesBody Length:0.540 inchesBody Outside Diameter:0.375 inchesOperating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:3.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 185.0 volts dc blankThread Size:
Body Length:         0.540 inches         Body Outside Diameter:         0.375 inches         Operating Tempurature Range:         -55.0/+85.0 degrees celsius         Source Impedance Rating Per Function:         50.0 ohms blank         Load Impedance Per Function:         50.0 ohms blank         Power Line Frequency Rating Per Function In Hertz:         400.0 blank         Operating Current Rating Per Function In Amps:         3.0 blank         Principal Circuitry Type Per Function:         Inductance-capacitance blank         Mounting Facility Screw Thread Series Designator:         Unf         Hermetically sealed         Mounting Facility Type And Quantity:         1 threaded bushing         Functional Terminal Type And Quantity:         1 tab, solder lug output 2nd function         Operating Voltage Rating And Type Per Function:         115.0 volts ac blank and 185.0 volts dc blank
0.540 inches Body Outside Diameter: 0.375 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Body Outside Diameter:0.375 inchesOperating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:3.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 185.0 volts dc blank
0.375 inches Operating Tempurature Range: -55.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Operating Tempurature Range:-55.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms blankLoad Impedance Per Function:50.0 ohms blankPower Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:3.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 185.0 volts dc blank
<ul> <li>-55.0/+85.0 degrees celsius</li> <li>Source Impedance Rating Per Function:</li> <li>50.0 ohms blank</li> <li>Load Impedance Per Function:</li> <li>50.0 ohms blank</li> <li>Power Line Frequency Rating Per Function In Hertz:</li> <li>400.0 blank</li> <li>Operating Current Rating Per Function In Amps:</li> <li>3.0 blank</li> <li>Principal Circuitry Type Per Function:</li> <li>Inductance-capacitance blank</li> <li>Mounting Facility Screw Thread Series Designator:</li> <li>Unf</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 185.0 volts dc blank</li> </ul>
Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Load Impedance Per Function: 50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
50.0 ohms blank Power Line Frequency Rating Per Function In Hertz: 400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Power Line Frequency Rating Per Function In Hertz:400.0 blankOperating Current Rating Per Function In Amps:3.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 185.0 volts dc blank
400.0 blank Operating Current Rating Per Function In Amps: 3.0 blank Principal Circuitry Type Per Function: Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Operating Current Rating Per Function In Amps:3.0 blankPrincipal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 185.0 volts dc blank
<ul> <li>3.0 blank</li> <li>Principal Circuitry Type Per Function:</li> <li>Inductance-capacitance blank</li> <li>Mounting Facility Screw Thread Series Designator:</li> <li>Unf</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 185.0 volts dc blank</li> </ul>
Principal Circuitry Type Per Function:Inductance-capacitance blankMounting Facility Screw Thread Series Designator:UnfInclosure Type:Hermetically sealedMounting Facility Type And Quantity:1 threaded bushingFunctional Terminal Type And Quantity:1 tab, solder lug output 2nd functionOperating Voltage Rating And Type Per Function:115.0 volts ac blank and 185.0 volts dc blank
Inductance-capacitance blank Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Mounting Facility Screw Thread Series Designator: Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Unf Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug output 2nd function Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
<ul> <li>Mounting Facility Type And Quantity:</li> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 185.0 volts dc blank</li> </ul>
<ol> <li>1 threaded bushing</li> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 185.0 volts dc blank</li> </ol>
<ul> <li>Functional Terminal Type And Quantity:</li> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 185.0 volts dc blank</li> </ul>
<ul> <li>1 tab, solder lug output 2nd function</li> <li>Operating Voltage Rating And Type Per Function:</li> <li>115.0 volts ac blank and 185.0 volts dc blank</li> </ul>
Operating Voltage Rating And Type Per Function: 115.0 volts ac blank and 185.0 volts dc blank
115.0 volts ac blank and 185.0 volts dc blank
Thread Size:
0.250 inches
Maximum Dielectric Withstanding Dc Voltage:
370.0 volts at sea level
Special Features:
Inductor at mounting end
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5915-00-481-5081

Radio Frequency Interference Filter - Page 2 of 2

**Fiig:** A047b0

