

View Online at <https://aerobasegroup.com/nsn/5915-00-482-7151>

Overall Length:

Between 4.588 inches and 4.597 inches

Overall Height:

Between 0.874 inches and 0.884 inches

Body Length:

4.000 inches

Body Width:

Between 2.251 inches and 2.260 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.176 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Reference Frequency Per Function:

200.0 kilohertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

80045

Input Terminal Identification:

2112-06-4

Output Terminal Manufacturer Code:

80045

Output Terminal Identification:

2112-06-4

Inclosure Type:

Encapsulated

Mounting Facility Type And Quantity:

4 unthreaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

6.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

160.00 kilohertz blank and 179.00 kilohertz blank and 220.00 kilohertz blank and 260.00 kilohertz blank

Frequency Band Width Per Function:

179.00 kilohertz blank and 220.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 6.0 blank and 6.0 blank and 60.0 blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Test Data Document:

80045-es361834 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0