

View Online at <https://aerobasegroup.com/nsn/5915-00-483-0132>

**Overall Height:**

1.750 inches

**Body Length:**

1.000 inches

**Body Width:**

1.000 inches

**Body Height:**

1.375 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Operating Temperature Range:**

-54.0/+71.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.5 kilohertz blank

**Input Impedance Per Function W/load:**

1.0 kilohms blank

**Output Impedance Per Function W/source Across Input:**

1.0 kilohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.0 blank

**Functional Terminal Type And Quantity:**

1 wire hook output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

750.00 hertz blank and 1.44 kilohertz blank and 1.56 kilohertz blank and 3.00 kilohertz blank

**Thread Size:**

0.112 inches

**Frequency Band Width Per Function:**

1.44 kilohertz blank and 1.56 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

40.0 blank and 6.0 blank and 6.0 blank and 40.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0