

View Online at <https://aerobasegroup.com/nsn/5915-00-484-1128>

Overall Height:

3.031 inches

Body Length:

1.625 inches

Body Width:

1.625 inches

Body Height:

2.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.000 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

5.075 kilohertz blank

Source Impedance Rating Per Function:

500.0 ohms blank

Load Impedance Per Function:

8.2 kilohms blank

Input Impedance Per Function W/load:

10.0 kilohms blank

Output Impedance Per Function W/source Across Input:

150.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

3 wire hook output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

0.00 hertz blank and 58.00 hertz blank and 150.00 hertz blank and 10.00 kilohertz blank

Thread Size:

0.138 inches

Frequency Band Width Per Function:

150.00 hertz blank and 10.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

60.0 blank and 60.0 blank and 3.0 blank and 3.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0