Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-484-6174

| Overall Length: | |
|--|--|
| 8.500 inches | |
| Body Length: | |
| 7.000 inches | |
| Body Width: | |
| 3.250 inches | |
| Body Height: | |
| 6.250 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | |
| 6.500 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | |
| 5.250 inches | |
| Operating Tempurature Range: | |
| +0.0/+55.0 degrees celsius | |
| Source Impedance Rating Per Function: | |
| 50.0 ohms 2nd radio interference | |
| Load Impedance Per Function: | |
| 50.0 ohms 2nd radio interference | |
| Power Line Frequency Rating Per Function In Hertz: | |
| 60.0 2nd radio interference | |
| Operating Current Rating Per Function In Amps: | |
| 70.0 2nd radio interference | |
| Mounting Facility Screw Thread Series Designator: | |
| Unf | |
| Inclosure Type: | |
| Encased | |
| Mounting Facility Type And Quantity: | |
| 6 threaded hole | |
| Functional Terminal Type And Quantity: | |
| 2 threaded stud input 1st function | |
| Operating Voltage Rating And Type Per Function: | |
| 120.0 volts ac 2nd radio interference 2nd function | |
| Thread Size: | |
| 0.190 inches | |
| Body Material: | |
| Metal | |
| Unpackaged Unit Weight: | |
| 10.000 pounds | |
| Style Designator: | |
| Rectangular terminal/terminals on opposite surfaces | |
| Shelf Life: | |
| N/a | |
| | |

Radio Frequency Interference Filter - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0