

View Online at <https://aerobasegroup.com/nsn/5915-00-486-7050>

Overall Height:

1.781 inches

Body Length:

0.734 inches

Body Width:

0.734 inches

Body Height:

1.406 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

Reference Frequency Per Function:

22.0 kilohertz blank

Source Impedance Rating Per Function:

100.0 kilohms blank

Load Impedance Per Function:

100.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

12.54 kilohertz blank and 20.35 kilohertz blank and 23.65 kilohertz blank and 38.50 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

20.35 kilohertz blank and 23.65 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 3.0 blank and 3.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Test Data Document:

10001-2641158 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0