## NSN 5915-00-491-2536

32.439 megahertz blank and 32.449 megahertz blank

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-491-2536

Overall Height:
1.406 inches
Body Length:
1.750 inches
Body Width:
1.250 inches
Body Height:
1.031 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.250 inches
Vibration Resistance Range In Hertz:
+5.0/+33.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.750 inches
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Reference Frequency Per Function:
32.444 megahertz blank
Input Impedance Per Function W/load:
100.0 ohms blank
Output Impedance Per Function W/source Across Input:
100.0 ohms blank
Principal Circuitry Type Per Function:
Crystal blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
3 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
8.0 blank
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Specified Frequencies Of Discrimination Per Function:
$32.429 \ megahertz \ blank \ and \ 32.439 \ megahertz \ blank \ and \ 32.459 \ megahertz \ blank \ and \ and$
Thread Size:
0.112 inches
Body Material:
Metal
Frequency Band Width Per Function:

## NSN 5915-00-491-2536

Band Pass Filter - Page 2 of 2



10.0 blank and 1.0 blank and 1.0 blank and 10.0 blank

**Style Designator:** 

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0