

View Online at <https://aerobasegroup.com/nsn/5915-00-491-6324>

Overall Height:

1.750 inches

Body Length:

1.000 inches

Body Width:

1.000 inches

Body Height:

1.375 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Operating Temperature Range:

-54.0/+71.0 degrees celsius

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

2.425 kilohertz blank

Input Impedance Per Function W/load:

1.0 kilohms blank

Output Impedance Per Function W/source Across Input:

1.0 kilohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

1 wire hook output 2nd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

1.212 kilohertz blank and 2.365 kilohertz blank and 2.485 kilohertz blank and 4.850 kilohertz blank

Thread Size:

0.112 inches

Frequency Band Width Per Function:

2.365 kilohertz blank and 2.485 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

40.0 blank and 6.0 blank and 6.0 blank and 40.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0