

View Online at https://aerobasegroup.com/nsn/5915-00-491-9185

Overall Height:2.680 inchesBody Length:2.000 inchesBody Width:1.500 inchesBody Height:2.500 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Length1.500 inchesOperating Tempurature Range:+0.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 2nd radio interferenceOperating Current Rating Per Function In Amps:3.0 2nd radio interference96906Output Terminal Identification:Mostlofe-57sMounting Facility Screw Thread Series Designator:UncIncoustre Type:Hermetically sealedMounting Facility Type And Quantity:2 threaded stud
Body Length: 2.000 inches Body Width: 1.500 inches Body Height: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches Operating Tempurature Range: 4.0.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
2.000 inches Body Width: 1.500 inches Body Height: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches Operating Tempurature Range: 4.00/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Incoure Type: Hermetically sealed
Body Width: 1.500 inches Body Height: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
1.500 inches Body Height: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches Operating Tempurature Range: 4.00/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Cutput Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Hermetically sealed
Body Height: 2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Hermetically sealed Mounting Facility Type And Quantity:
2.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.500 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Hermetically sealed Mounting Facility Type And Quantity:
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:1.500 inchesOperating Tempurature Range:+0.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 2nd radio interferenceOperating Current Rating Per Function In Amps:3.0 2nd radio interferenceOutput Terminal Manufacturer Code:96906Output Terminal Identification:Ms3106-4s-7sMounting Facility Screw Thread Series Designator:UncInclosure Type:Hermetically sealedMounting Facility Type And Quantity:
1.500 inches Operating Tempurature Range: +0.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Operating Tempurature Range:+0.0/+85.0 degrees celsiusSource Impedance Rating Per Function:50.0 ohms 2nd radio interferenceLoad Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 2nd radio interferenceOperating Current Rating Per Function In Amps:3.0 2nd radio interferenceOutput Terminal Manufacturer Code:96906Output Terminal Identification:Ms3106-4s-7sMounting Facility Screw Thread Series Designator:UncInclosure Type:Hermetically sealedMounting Facility Type And Quantity:
+0.0/+85.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Source Impedance Rating Per Function: 50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
50.0 ohms 2nd radio interference Load Impedance Per Function: 50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Load Impedance Per Function:50.0 ohms 2nd radio interferencePower Line Frequency Rating Per Function In Hertz:60.0 2nd radio interferenceOperating Current Rating Per Function In Amps:3.0 2nd radio interferenceOutput Terminal Manufacturer Code:96906Output Terminal Identification:Ms3106-4s-7sMounting Facility Screw Thread Series Designator:UncInclosure Type:Hermetically sealedMounting Facility Type And Quantity:
50.0 ohms 2nd radio interference Power Line Frequency Rating Per Function In Hertz: 60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Power Line Frequency Rating Per Function In Hertz:60.0 2nd radio interferenceOperating Current Rating Per Function In Amps:3.0 2nd radio interferenceOutput Terminal Manufacturer Code:96906Output Terminal Identification:Ms3106-4s-7sMounting Facility Screw Thread Series Designator:UncInclosure Type:Hermetically sealedMounting Facility Type And Quantity:
60.0 2nd radio interference Operating Current Rating Per Function In Amps: 3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Operating Current Rating Per Function In Amps:3.0 2nd radio interferenceOutput Terminal Manufacturer Code:96906Output Terminal Identification:Ms3106-4s-7sMounting Facility Screw Thread Series Designator:UncInclosure Type:Hermetically sealedMounting Facility Type And Quantity:
3.0 2nd radio interference Output Terminal Manufacturer Code: 96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Output Terminal Manufacturer Code:96906Output Terminal Identification:Ms3106-4s-7sMounting Facility Screw Thread Series Designator:UncInclosure Type:Hermetically sealedMounting Facility Type And Quantity:
96906 Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Output Terminal Identification: Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Ms3106-4s-7s Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Hermetically sealed Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
2 threaded stud
Functional Terminal Type And Quantity:
2 tab, solder lug input 1st function
Operating Voltage Rating And Type Per Function:
220.0 volts ac 1st radio interference 1st function
Thread Size:
Thread Size: 0.138 inches
0.138 inches
0.138 inches Style Designator:
0.138 inches Style Designator: Rectangular terminal/terminals on opposite surfaces

--



Demilitarization:

No

Fiig:

A047b0