

View Online at <https://aerobasegroup.com/nsn/5915-00-492-1050>

Vibration Resistance Range In Hertz:

+30.0/+2000.0

Operating Temperature Range:

-54.0/+125.0 degrees celsius

Average Life Rating In Hours:

2000.0

Reference Frequency Per Function:

13.85 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Voltage Standing Wave Ratio Per Function:

2.0 blank

Inclosure Type:

Encased

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

9.50 gigahertz blank and 9.70 gigahertz blank and 18.00 gigahertz blank and 18.60 gigahertz blank

Frequency Band Width Per Function:

9.70 gigahertz blank and 18.00 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

30.0 blank and 1.0 blank and 1.0 blank and 30.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

9.7 gigahertz blank and 18.0 gigahertz blank

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0