NSN 5915-00-494-4777

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-494-4777

A II 11					
Overall Height:					
0.784 inches					
Body Length:					
3.485 inches					
Body Width:					
1.185 inches					
Body Height:					
0.628 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:					
3.280 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:					
0.578 inches					
Reference Frequency Per Function:					
100.0 hertz blank					
Input Impedance Per Function W/load:					
5.1 kilohms blank					
Output Impedance Per Function W/source Across Input:					
9.1 kilohms blank					
Mounting Facility Screw Thread Series Designator:					
Unc					
Inclosure Type:					
Encased					
Mounting Facility Type And Quantity:					
4 threaded hole					
Insertion Loss At Reference Frequency Per Function In Decibels:					
0.5 blank					
0.5 blank Functional Terminal Type And Quantity:					
Functional Terminal Type And Quantity:					
Functional Terminal Type And Quantity: 1 pin output 2nd function					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function:					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size:					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size: 0.112 inches					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size: 0.112 inches Body Material:					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size: 0.112 inches Body Material: Metal					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size: 0.112 inches Body Material: Metal Frequency Band Width Per Function:					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size: 0.112 inches Body Material: Metal Frequency Band Width Per Function: 1.00 hertz blank and 200.00 hertz blank					
Functional Terminal Type And Quantity: 1 pin output 2nd function Specified Frequencies Of Discrimination Per Function: 1.00 hertz blank and 200.00 hertz blank and 800.00 hertz blank and 1.20 kilohertz blank Thread Size: 0.112 inches Body Material: Metal Frequency Band Width Per Function: 1.00 hertz blank and 200.00 hertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:					

N/a

Shelf Life:

NSN 5915-00-494-4777

Low Pass Filter - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A047b0