

View Online at <https://aerobasegroup.com/nsn/5915-00-495-7327>

Overall Length:

5.170 inches

Body Outside Diameter:

0.755 inches

Operating Temperature Range:

-18.0/+70.0 degrees celsius

Average Life Rating In Hours:

30000.0

Reference Frequency Per Function:

666.0 megahertz blank

Load Impedance Per Function:

50.0 ohms blank

Input Impedance Per Function W/load:

50.0 ohms blank

Output Impedance Per Function W/source Across Input:

50.0 ohms blank

Input Terminal Manufacturer Code:

23042

Input Terminal Identification:

K

Output Terminal Manufacturer Code:

23042

Output Terminal Identification:

L

Voltage Standing Wave Ratio Per Function:

1.25 blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

1.8 blank

Functional Terminal Type And Quantity:

1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

556.00 megahertz blank and 654.00 megahertz blank and 678.00 megahertz blank and 776.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

654.00 megahertz blank and 678.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

80.0 blank and 3.0 blank and 3.0 blank and 80.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

654.0 megahertz blank and 678.0 megahertz blank

Unpackaged Unit Weight:

5.000 ounces

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0