NSN 5915-00-499-1990

Band Pass-low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-499-1990

| Overall Height: |
|--|
| 1.150 inches |
| Body Length: |
| 4.020 inches |
| Body Width: |
| 2.020 inches |
| Body Height: |
| 0.900 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.683 inches |
| Operating Tempurature Range: |
| +10.0/+50.0 degrees celsius |
| Reference Frequency Per Function: |
| 2.95 7th radio interference any acceptable |
| Input Impedance Per Function W/load: |
| 2.61 kilohms single low pass |
| Output Impedance Per Function W/source Across Input: |
| 2.0 kilohms single low pass |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance-resistance single low pass |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 0.5 single band pass |
| Functional Terminal Type And Quantity: |
| 3 pin input 1st function |
| Specified Frequencies Of Discrimination Per Function: |
| 59.00 kilohertz single band pass and 60.50 kilohertz single band pass and 64.00 kilohertz single band pass and 64.50 kilohertz single band |
| pass |
| Thread Size: |
| 0.112 inches |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 25.0 single band pass and 0.5 single band pass and 0.5 single band pass and 54.0 single band pass |
| Style Designator: |
| Rectangular terminal/terminals on one surface |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5915-00-499-1990

Band Pass-low Pass Filter - Page 2 of 2



Demilitarization:

No

Fiig:

A047b0