

View Online at <https://aerobasegroup.com/nsn/5915-00-501-4056>

**Overall Length:**

3.156 inches

**Overall Height:**

3.156 inches

**Overall Width:**

2.031 inches

**Body Length:**

2.031 inches

**Body Width:**

1.453 inches

**Body Height:**

2.594 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.812 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

1.2 kilohertz blank

**Source Impedance Rating Per Function:**

600.0 ohms blank

**Load Impedance Per Function:**

600.0 ohms blank

**Input Impedance Per Function W/load:**

600.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

600.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.6 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug output 2nd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

1.00 hertz blank and 2.40 kilohertz blank and 4.00 kilohertz blank and 5.00 kilohertz blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 hertz blank and 2.40 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 1.0 blank and 27.0 blank and 37.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A047b0