

View Online at <https://aerobasegroup.com/nsn/5915-00-501-4135>

Overall Height:

3.562 inches

Body Length:

1.719 inches

Body Width:

1.719 inches

Body Height:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.125 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.125 inches

Operating Temperature Range:

-65.0/+185.0 degrees fahrenheit

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

68.0 kilohertz blank

Input Impedance Per Function W/load:

100.0 kilohms blank

Output Impedance Per Function W/source Across Input:

100.0 kilohms blank

Principal Circuitry Type Per Function:

Crystal blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

2.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Specified Frequencies Of Discrimination Per Function:

67.00 kilohertz blank and 67.995 kilohertz blank and 68.025 kilohertz blank and 69.000 kilohertz blank

Thread Size:

0.190 inches

Frequency Band Width Per Function:

67.995 kilohertz blank and 68.025 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

50.0 blank and 2.0 blank and 2.0 blank and 40.0 blank

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0