NSN 5915-00-501-4154

66.00 kilohertz blank and 70.00 kilohertz blank

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-00-501-4154

Overall Height:
3.150 inches
Body Length:
2.380 inches
Body Width:
1.450 inches
Body Height:
2.590 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.312 inches
Vibration Resistance Range In Hertz:
+10.0/+55.0
Operating Tempurature Range:
-65.0/+150.0 degrees fahrenheit
Average Life Rating In Hours:
10000.0
Reference Frequency Per Function:
68.0 kilohertz blank
Input Impedance Per Function W/load:
600.0 ohms blank
Output Impedance Per Function W/source Across Input:
225.0 kilohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance-resistance blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded stud
Insertion Loss At Reference Frequency Per Function In Decibels:
3.0 blank
Functional Terminal Type And Quantity:
2 tab, solder lug ground 3rd function
Specified Frequencies Of Discrimination Per Function:
55.00 kilohertz blank and 66.00 kilohertz blank and 70.00 kilohertz blank and 75.00 kilohertz blank
Thread Size:
0.190 inches
Body Material:
Metal
Frequency Band Width Per Function:

NSN 5915-00-501-4154

Band Pass Filter - Page 2 of 2



Discrimination At Specificationified Frequencies Per Function In Decibels:

35.0 blank and 3.0 blank and 3.0 blank and 15.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0