

View Online at <https://aerobasegroup.com/nsn/5915-00-501-4155>

**Overall Height:**

3.062 inches

**Body Length:**

4.844 inches

**Body Width:**

1.812 inches

**Body Height:**

2.531 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.188 inches

**Vibration Resistance Range In Hertz:**

+10.0/+55.0

**Operating Temperature Range:**

-65.0/+185.0 degrees fahrenheit

**Average Life Rating In Hours:**

10000.0

**Reference Frequency Per Function:**

120.0 kilohertz blank

**Input Impedance Per Function W/load:**

130.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

40.0 kilohms blank

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded stud

**Insertion Loss At Reference Frequency Per Function In Decibels:**

4.0 blank

**Functional Terminal Type And Quantity:**

2 tab, solder lug ground 3rd function

**Maximum Dielectric Withstanding Ac Rms Voltage:**

500.0 volts at sea level

**Specified Frequencies Of Discrimination Per Function:**

112.00 kilohertz blank and 116.00 kilohertz blank and 124.00 kilohertz blank and 128.00 kilohertz blank

**Thread Size:**

0.190 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

116.00 kilohertz blank and 124.00 kilohertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

65.0 blank and 40.0 blank and 40.0 blank and 65.0 blank

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0