

View Online at <https://aerobasegroup.com/nsn/5915-00-501-4155>

Overall Height:

3.062 inches

Body Length:

4.844 inches

Body Width:

1.812 inches

Body Height:

2.531 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.188 inches

Vibration Resistance Range In Hertz:

+10.0/+55.0

Operating Temperature Range:

-65.0/+185.0 degrees fahrenheit

Average Life Rating In Hours:

10000.0

Reference Frequency Per Function:

120.0 kilohertz blank

Input Impedance Per Function W/load:

130.0 ohms blank

Output Impedance Per Function W/source Across Input:

40.0 kilohms blank

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

4.0 blank

Functional Terminal Type And Quantity:

2 tab, solder lug ground 3rd function

Maximum Dielectric Withstanding Ac Rms Voltage:

500.0 volts at sea level

Specified Frequencies Of Discrimination Per Function:

112.00 kilohertz blank and 116.00 kilohertz blank and 124.00 kilohertz blank and 128.00 kilohertz blank

Thread Size:

0.190 inches

Body Material:

Metal

Frequency Band Width Per Function:

116.00 kilohertz blank and 124.00 kilohertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

65.0 blank and 40.0 blank and 40.0 blank and 65.0 blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0