

View Online at <https://aerobasegroup.com/nsn/5915-00-502-4460>

**Overall Length:**

2.500 inches

**Overall Height:**

0.350 inches

**Body Length:**

1.500 inches

**Body Width:**

0.700 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.100 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Reference Frequency Per Function:**

16.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Input Impedance Per Function W/load:**

50.0 ohms blank

**Output Impedance Per Function W/source Across Input:**

50.0 ohms blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.5 blank

**Functional Terminal Type And Quantity:**

2 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

2.00 megahertz blank and 30.00 megahertz blank and 79.00 megahertz blank and 200.00 megahertz blank

**Frequency Band Width Per Function:**

2.00 megahertz blank and 30.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 1.0 blank and 50.0 blank and 50.0 blank

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Test Data Document:**

13499-580-7037-001 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0